



Typ / Type: RS 160		Art.-Nr. / Art.-No.: F00-16051	
U	230V (50Hz)	Δpfa min	-- Pa
P1	0,07 kW	ΔI	-- %
IN	0.30 A	IA / IN	1.5
n	2400 min-1	▲	IP44
C400V	2 μF	✱	01.009
tr	70 °C	■	3.0 kg

Typ / Type: RS 160 L		Art.-Nr. / Art.-No.: F00-16060	
U	230V (50Hz)	Δpfa min	-- Pa
P1	0,115 kW	ΔI	-- %
IN	0.49 A	IA / IN	1.5
n	2440 min-1	▲	IP44
C400V	3 μF	✱	01.009
tr	50 °C	■	3.2 kg

Geräusche / Sound levels:

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA2 [dB(A)] Gehäuse / casing	33	40	43	43	44	32	23
LWA5 [dB(A)] Ansaugseite / inlet side	40	54	55	55	54	50	41
LWA6 [dB(A)] Ausblasseite / outlet side	37	49	47	51	52	49	39

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA2 [dB(A)] Gehäuse / casing	41	43	51	50	47	39	30
LWA5 [dB(A)] Ansaugseite / inlet side	45	58	61	63	62	59	50
LWA6 [dB(A)] Ausblasseite / outlet side	43	55	55	60	62	58	50

Schaltbild / Wiring diagram:

Maße / Dimensions:

(alle Maße in mm / all dimensions in mm)

