



Typ / Type: RS 250		Art.-Nr. / Art.-No.: F00-25051	
U	230V (50Hz)	Δpfa min	-- Pa
P1	0,115 kW	ΔI	-- %
IN	0.50 A	IA / IN	1.5
n	2450 min-1	▲	IP44
C400V	3 μF	✱	01.009
tr	50 °C	■	3.4 kg

Typ / Type: RS 250 L		Art.-Nr. / Art.-No.: F00-25060	
U	230V (50Hz)	Δpfa min	-- Pa
P1	0,160 kW	ΔI	14 %
IN	0.65 A	IA / IN	1.8
n	2560 min-1	▲	IP44
C400V	5 μF	✱	01.009
tr	55 °C	■	3.7 kg

Geräusche / Sound levels:

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA2 [dB(A)] Gehäuse / casing	37	44	44	45	45	39	29
LWA5 [dB(A)] Ansaugseite / inlet side	45	55	58	60	60	55	45
LWA6 [dB(A)] Ausblasseite / outlet side	44	55	53	58	60	55	46

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA2 [dB(A)] Gehäuse / casing	40	45	52	48	46	40	31
LWA5 [dB(A)] Ansaugseite / inlet side	50	60	61	63	61	58	47
LWA6 [dB(A)] Ausblasseite / outlet side	49	58	58	62	62	57	47

Schaltbild / Wiring diagram:

Maße / Dimensions:

(alle Maße in mm / all dimensions in mm)

