



Typ / Type: RS 315		Art.-Nr. / Art.-No.: F00-31551	
U	230V (50Hz)	Δp _{fa} min	-- Pa
P ₁	0,22 kW	Δl	14 %
I _N	0,95 A	I _A / I _N	1,9
n	2540 min ⁻¹		IP44
C _{400V}	5 μF		01.009
t _R	55 °C		5,7 kg

Typ / Type: RS 315 L		Art.-Nr. / Art.-No.: F00-31560	
U	230V (50Hz)	Δp _{fa} min	-- Pa
P ₁	0,30 kW	Δl	-- %
I _N	1,30 A	I _A / I _N	1,7
n	2390 min ⁻¹		IP44
C _{400V}	8 μF		01.009
t _R	45 °C		5,8 kg

Geräusche / Sound levels:

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	43	46	48	48	47	41	28
LWA ₅ [dB(A)] Ansaugseite / inlet side	50	59	64	64	63	62	55
LWA ₆ [dB(A)] Ausblasseite / outlet side	51	60	62	65	68	65	58

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	41	49	51	51	50	47	38
LWA ₅ [dB(A)] Ansaugseite / inlet side	47	59	68	69	67	66	61
LWA ₆ [dB(A)] Ausblasseite / outlet side	43	55	62	63	64	60	57

Schaltbild / Wiring diagram:

Maße / Dimensions:

(alle Maße in mm / all dimensions in mm)

