



Typ / Type : Z 250 E1		Art.-Nr. / Art.-No. : F05-25007	
U	230V (50Hz)	Δpfa min	-- Pa
P ₁	0,27 kW	ΔI	-- %
I _N	1.15 A	I _A / I _N	1.2
n	1825 min ⁻¹		IP44
C _{400V}	6 μF		01.009
t _R	55 °C		15.5 kg

Typ / Type : Z 250 E2		Art.-Nr. / Art.-No. : F05-25008	
U	230V (50Hz)	Δpfa min	80 Pa
P ₁	0,32 kW	ΔI	-- %
I _N	1.4 A	I _A / I _N	1.2
n	2130 min ⁻¹		IP44
C _{400V}	10 μF		01.009
t _R	40 °C		18.5 kg

Geräusche / Sound levels:

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA2 [dB(A)]	Gehäuse / casing	44	43	39	37	34	29	24
LWA5 [dB(A)]	Ansaugseite / inlet side	49	47	44	43	42	40	33
LWA6 [dB(A)]	Ausblasseite / outlet side	54	60	63	66	68	63	57

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA2 [dB(A)]	Gehäuse / casing	48	46	41	39	39	34	27
LWA5 [dB(A)]	Ansaugseite / inlet side	50	51	48	46	46	45	36
LWA6 [dB(A)]	Ausblasseite / outlet side	51	60	64	70	71	66	61

Maße / Dimensions:

(alle Maße in mm / all dimensions in mm)

