



Typ / Type: UNO-50-355-4 D		Art.-Nr. / Art.-No.: F08-35504	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,33 kW	ΔI	-- %
I _N	0.7 A	I _A / I _N	3.3
n	1355 min ⁻¹		IP54
C _{400V}	-- μ F		01.006
t _R	40 °C		33 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

Typ / Type: UNO-50-355-4-4 D		Art.-Nr. / Art.-No.: F08-35501	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,33/0,23 kW	ΔI	-- %
I _N	0.7/0.37 A	I _A / I _N	3.3
n	1355/1115 min ⁻¹		IP54
C _{400V}	-- μ F		01.045
t _R	40 °C		33 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-8	-4	-5	-10	-15	-26	-29
LWA ₅ [dB(A)] Ansaugseite / inlet side	-13	-9	-4	-6	-9	-13	-24
LWA ₆ [dB(A)] Ausblasseite / outlet side	-12	-11	-5	-5	-8	-12	-25

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-8	-4	-5	-10	-15	-26	-29
LWA ₅ [dB(A)] Ansaugseite / inlet side	-13	-9	-4	-6	-9	-13	-24
LWA ₆ [dB(A)] Ausblasseite / outlet side	-12	-11	-5	-5	-8	-12	-25

