



Typ / Type: UNO-67-400-4 D		Art.-Nr. / Art.-No.: F08-40004	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,48 kW	ΔI	-- %
I _N	0.9 A	I _A / I _N	3.2
n	1335 min ⁻¹		IP54
C _{400V}	-- μ F		01.006
t _R	50 °C		49 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

Typ / Type: UNO-67-400-4-4 D		Art.-Nr. / Art.-No.: F08-40001	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,48/0,34 kW	ΔI	-- %
I _N	0.9/0.55 A	I _A / I _N	3.2
n	1335/1040 min ⁻¹		IP54
C _{400V}	-- μ F		01.045
t _R	50 °C		49 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-4	-4	-9	-13	-16	-21	-29
LWA ₅ [dB(A)] Ansaugseite / inlet side	-15	-6	-4	-8	-10	-13	-20
LWA ₆ [dB(A)] Ausblasseite / outlet side	-10	-9	-7	-4	-9	-14	-23

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-4	-4	-9	-13	-16	-21	-29
LWA ₅ [dB(A)] Ansaugseite / inlet side	-15	-6	-4	-8	-10	-13	-20
LWA ₆ [dB(A)] Ausblasseite / outlet side	-10	-9	-7	-4	-9	-14	-23

