



Typ / Type: UNO-67-500-4 D		Art.-Nr. / Art.-No.: F08-50011	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	1,80 kW	ΔI	8 %
I _N	3.70 A	I _A / I _N	4.8
n	1380 min ⁻¹		IP54
C _{400V}	-- μ F		01.006
t _R	40 °C		66 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

Typ / Type: UNO-67-500-4-4 D		Art.-Nr. / Art.-No.: F08-50012	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	1,8/1,3 kW	ΔI	8 %
I _N	3.7/2.1 A	I _A / I _N	4.8
n	1380/1190 min ⁻¹		IP54
C _{400V}	-- μ F		01.045
t _R	40 °C		66 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-6	-3	-8	-9	-18	-24	-32
LWA ₅ [dB(A)] Ansaugseite / inlet side	-19	-7	-6	-6	-8	-11	-20
LWA ₆ [dB(A)] Ausblasseite / outlet side	-20	-11	-8	-3	-9	-13	-22

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-6	-3	-8	-9	-18	-24	-32
LWA ₅ [dB(A)] Ansaugseite / inlet side	-19	-7	-6	-6	-8	-11	-20
LWA ₆ [dB(A)] Ausblasseite / outlet side	-20	-11	-8	-3	-9	-13	-22

