



Typ / Type: UNO-67-500-6 D		Art.-Nr. / Art.-No.: F08-50013	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,52 kW	ΔI	-- %
I _N	0,95 A	I _A / I _N	2,9
n	860 min ⁻¹		IP54
C _{400V}	-- μF		01.006
t _R	55 °C		57 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

Typ / Type: UNO-67-500-6-6 D		Art.-Nr. / Art.-No.: F08-50014	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,52/1,3 kW	ΔI	-- %
I _N	0,95/0,55 A	I _A / I _N	2,9
n	860/640 min ⁻¹		IP54
C _{400V}	-- μF		01.045
t _R	55 °C		57 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-3	-4	-13	-15	-18	-23	-30
LWA ₅ [dB(A)] Ansaugseite / inlet side	-12	-8	-3	-5	-6	-11	-22
LWA ₆ [dB(A)] Ausblasseite / outlet side	-17	-15	-5	-4	-7	-15	-25

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-3	-4	-13	-15	-18	-23	-30
LWA ₅ [dB(A)] Ansaugseite / inlet side	-12	-8	-3	-5	-6	-11	-22
LWA ₆ [dB(A)] Ausblasseite / outlet side	-17	-15	-5	-4	-7	-15	-25

