



Typ / Type: UNO-80-560-6 D		Art.-Nr. / Art.-No.: F08-56012	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,86 kW	ΔI	-- %
I _N	2.05 A	I _A / I _N	2.9
n	870 min-1		IP54
C _{400V}	-- μ F		01.006
t _R	50 °C		82 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

Typ / Type: UNO-80-560-6-6 D		Art.-Nr. / Art.-No.: F08-56013	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,86/0,52 kW	ΔI	-- %
I _N	2.05/0.95 A	I _A / I _N	2.9
n	870/690 min-1		IP54
C _{400V}	-- μ F		01.045
t _R	50 °C		82 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _M [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-3	-4	-13	-15	-18	-23	-30
LWA ₅ [dB(A)] Ansaugseite / inlet side	-12	-8	-3	-5	-6	-11	-22
LWA ₆ [dB(A)] Ausblasseite / outlet side	-17	-15	-5	-4	-7	-15	-25

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _M [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)] Gehäuse / casing	-3	-4	-13	-15	-18	-23	-30
LWA ₅ [dB(A)] Ansaugseite / inlet side	-12	-8	-3	-5	-6	-11	-22
LWA ₆ [dB(A)] Ausblasseite / outlet side	-17	-15	-5	-4	-7	-15	-25

