



Typ / Type : UNO-80-630-4 D		Art.-Nr. / Art.-No. : F08-63008	
U	400V (50Hz)	Δp_{fa} min	- Pa
P ₁	3.65 kW	ΔI	20 %
I _N	6.60 A	I _A / I _N	4.2
n	1380 min ⁻¹		IP54
C _{400V}	- μF		01.006
t _R	45 °C		105 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

Typ / Type : UNO-80-630-4-4 D		Art.-Nr. / Art.-No. : F08-63009	
U	400V (50Hz)	Δp_{fa} min	- Pa
P ₁	3.65/2.55 kW	ΔI	- %
I _N	6.6/4.45 A	I _A / I _N	4.2
n	1380/1120 min ⁻¹		IP54
C _{400V}	- μF		01.006
t _R	45 °C		105 kg

--- Kennlinie bei Nennspannung; bei axialer Durchströmung der Unobox / performance curve at rated voltage; at axial air flow in Unobox

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)]	Gehäuse / casing	-3	-4	-14	-15	-17	-21	-27
LWA ₅ [dB(A)]	Ansaugseite / inlet side	-19	-7	-6	-6	-8	-11	-20
LWA ₆ [dB(A)]	Ausblasseite / outlet side	-20	-11	-8	-3	-9	-13	-22

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA ₂ [dB(A)]	Gehäuse / casing	-3	-4	-14	-15	-17	-21	-27
LWA ₅ [dB(A)]	Ansaugseite / inlet side	-19	-7	-6	-6	-8	-11	-20
LWA ₆ [dB(A)]	Ausblasseite / outlet side	-20	-11	-8	-3	-9	-13	-22

