



Typ / Type: DV/DH 310K-6 E		Art.-No.: A00-31003 / A10-31003	
U	230V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,08 kW	ΔI	-- %
I _N	0,35 A	I _A / I _N	1,3
n	1050 min ⁻¹		IP44
C _{400V}	1,5 μ F		01.009
t _R	60 °C		9,5 kg

Typ / Type: DV/DH 310K-6-6 E		Art.-No.: A00-31009 / A10-31009	
U	230V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,08/0,04 kW	ΔI	-- %
I _N	0,35/0,16 A	I _A / I _N	1,3
n	1050/480 min ⁻¹		IP44
C _{400V}	1,5 μ F		01.020
t _R	60 °C		9,5 kg

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

