



Typ / Type : DV/DH 225-4 E		Art.-No. : A00-22506 / A10-22506	
U	230V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0.04 kW	ΔI	-- %
I _N	0.16 A	I _A / I _N	1.5
n	1320 min ⁻¹		IP44
C _{400V}	1.5 μ F		01.009
t _R	60 °C		4,5 kg

Typ / Type : DV/DH 225-4-4E		Art.-No. : A00-22509 / A00-22509	
U	230V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0.04/0.02 kW	ΔI	-- %
I _N	0.16/0.1 A	I _A / I _N	1.4
n	1320/1000 min ⁻¹		IP44
C _{400V}	1.5 μ F		01.020
t _R	60 °C		4,5 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-22	-11	-7	-7	-11	-13	-18
LWA6 [dB(A)]	Ausblasseite / outlet side	-22	-9	-6	-6	-6	-11	-15

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-22	-11	-7	-7	-11	-13	-18
LWA6 [dB(A)]	Ausblasseite / outlet side	-22	-9	-6	-6	-6	-11	-15

