







Typ / Type: DV/DH 280-2 E		Art.-No.: A00-28000 / A10-28000	
U	230V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,30 kW	ΔI	8 %
I _N	1.30 A	I _A / I _N	2.8
n	2330 min ⁻¹		IP44
C _{400V}	8 μ F		01.009
t _R	50 °C		9 kg

Typ / Type: DV/DH 280-4 E		Art.-No.: A00-28002 / A10-28002	
U	230V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,11 kW	ΔI	8 %
I _N	0.47 A	I _A / I _N	1.7
n	1290 min ⁻¹		IP44
C _{400V}	3 μ F		01.009
t _R	50 °C		9 kg

Geräusche / Sound levels:

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)] Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA ₆ [dB(A)] Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)] Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA ₆ [dB(A)] Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

