







Typ / Type : DV/DH 310L-4 D		Art.-No. : A00-31052 / A10-31052	
U	400V (50Hz)	Δpfa min	-- Pa
P1	0,15 kW	ΔI	-- %
IN	0,32 A	IA / IN	2,3
n	1320 min-1		IP44
C400V	-- μF		01.006
tr	50 °C		10 kg

Typ / Type : DV/DH 310L-4-4 D		Art.-No. : A00-31058 / A10-31058	
U	400V (50Hz)	Δpfa min	-- Pa
P1	0,15/0,09 kW	ΔI	-- %
IN	0,32/0,16 A	IA / IN	2,3
n	1320/1030 min-1		IP44
C400V	-- μF		01.045
tr	50 °C		10 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	f [Hz]						
	125	250	500	1K	2K	4K	8K
LWA5 [dB(A)] Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA6 [dB(A)] Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	f [Hz]						
	125	250	500	1K	2K	4K	8K
LWA5 [dB(A)] Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA6 [dB(A)] Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

