



Typ / Type: DV/DH 310L-4 E		Art.-No.: A00-31012 / A10-31012	
U	230V (50Hz)	Δpfa min	-- Pa
P1	0,15 kW	ΔI	-- %
IN	0,66 A	IA / IN	1,8
n	1300 min-1		IP44
C400V	4 μF		01.009
tr	50 °C		10 kg

Typ / Type: DV/DH 310L-4-4 E		Art.-No.: A00-31018 / A10-31018	
U	230V (50Hz)	Δpfa min	-- Pa
P1	0,15/0,07 kW	ΔI	-- %
IN	0,66/0,46 A	IA / IN	1,8
n	1300/740 min-1		IP44
C400V	4 μF		01.020
tr	50 °C		10 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

