



Typ / Type : DV/DH 355-4 D		Art.-No. : A00-35540 / A10-35540	
U	400V (50Hz)	Δpfa min	-- Pa
P ₁	0.27 kW	ΔI	-- %
I _N	0.55 A	I _A / I _N	2.7
n	1310 min ⁻¹		IP54
C _{400V}	-- μF		01.006
t _R	60 °C		19 kg

Typ / Type : DV/DH 355-4-4 D		Art.-No. : A00-35549 / A10-35549	
U	400V (50Hz)	Δpfa min	-- Pa
P ₁	0.27/0.18 kW	ΔI	-- %
I _N	0.55/0.30 A	I _A / I _N	2.7
n	1310/1040 min ⁻¹		IP54
C _{400V}	-- μF		01.045
t _R	60 °C		19 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-16	-10	-10	-7	-8	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-20	-11	-6	-4	-7	-13	-19

