



Typ / Type : DV/DH 400-4 D		Art.-No. : A00-40040 / A10-40040	
U	400V (50Hz)	Δpfa min	- Pa
P ₁	0.46 kW	ΔI	10 %
I _N	0.84 A	I _A / I _N	3.0
n	1340 min ⁻¹	▲	IP54
C _{400V}	- μF	★	01.006
t _R	40 °C	■	21 kg

Typ / Type : DV/DH 400-4-4 D		Art.-No. : A00-40049 / A10-40049	
U	400V (50Hz)	Δpfa min	- Pa
P ₁	0.43/0.27 kW	ΔI	- %
I _N	0.74/0.45 A	I _A / I _N	2.6
n	1275/895 min ⁻¹	▲	IP54
C _{400V}	- μF	★	01.045
t _R	40 °C	■	21 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

