



Typ / Type: DV/DH 400-4 E		Art.-No. : A00-40000 / A10-40000	
U	230V (50Hz)	Δpfa min	-- Pa
P ₁	0,52 kW	ΔI	16 %
I _N	2.43 A	I _A / I _N	2.65
n	1385 min ⁻¹		IP54
C _{400V}	12 μF		01.024
t _R	45 °C		22 kg

Typ / Type: DV/DH 400-6 E		Art.-No. : A00-40003 / A10-40003	
U	230V (50Hz)	Δpfa min	-- Pa
P ₁	0,19 kW	ΔI	12 %
I _N	0.88 A	I _A / I _N	2.5
n	920 min ⁻¹		IP54
C _{400V}	4 μF		01.024
t _R	60 °C		21 kg

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)] Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA ₆ [dB(A)] Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _m [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)] Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA ₆ [dB(A)] Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

