



Typ / Type: DV/DH 450-4 D		Art.-No.: A00-45040 / A10-45040	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,74 kW	ΔI	-- %
I _N	1.46 A	I _A / I _N	2.4
n	1240 min ⁻¹		IP54
C _{400V}	-- μ F		01.006
t _R	40 °C		27 kg

Typ / Type: DV/DH 450-4-4 D		Art.-No.: A00-45049 / A10-45049	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,74/0,39 kW	ΔI	-- %
I _N	1.46/0,75 A	I _A / I _N	2.4
n	1240/855 min ⁻¹		IP54
C _{400V}	-- μ F		01.045
t _R	40 °C		27 kg

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		f _M [Hz]						
		125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)]	Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA ₆ [dB(A)]	Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		f _M [Hz]						
		125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)]	Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA ₆ [dB(A)]	Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

