






Typ / Type : DVW/DHW 450-4 D		Art.-No. : A26-45061 / A36-45061	
U	400V (50Hz)	Δpfa min	-- Pa
P1	0,94 kW	ΔI	9 %
IN	1.70 A	IA / IN	3.3
n	1320 min-1		IP54
C400V	-- μF		01.006
tr	40 °C		29 kg

Type : DVW/DHW 450-4-4 D		Art.-No. : A26-45067 / A36-45067	
U	400V (50Hz)	Δpfa min	-- Pa
P1	0,94/0.62 kW	ΔI	-- %
IN	1.7/1.1 A	IA / IN	3.3
n	1320/990 min-1		IP54
C400V	-- μF		01.045
tr	40 °C		29 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA5 [dB(A)] Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA6 [dB(A)] Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA5 [dB(A)] Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA6 [dB(A)] Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

