



Type : DVW/DHW 500-4 D		Art.-No. : A26-50040 / A36-50040	
U	400V (50Hz)	Δp_{fa} min	- Pa
P ₁	1.8 kW	ΔI	11 %
I _N	3.5 A	I _A / I _N	4.0
n	1380 min ⁻¹		IP54
C _{400V}	- μ F		01.006
t _R	55 °C		39 kg

Type : DVW/DHW 500-4-4 D		Art.-No. : A26-50056 / A36-50056	
U	400V (50Hz)	Δp_{fa} min	- Pa
P ₁	1.8/1.3 kW	ΔI	- %
I _N	3.5/2.1 A	I _A / I _N	4.0
n	1380/1190 min ⁻¹		IP54
C _{400V}	- μ F		01.045
t _R	55 °C		39 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-17	-11	-11	-8	-9	-15	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-16	-8	-6	-5	-8	-14	-23

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-17	-11	-11	-8	-9	-15	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-16	-8	-6	-5	-8	-14	-23

