







Type : DVW/DHW 500-6 D		Art.-No. : A26-50046 / A36-50046	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,52 kW	ΔI	-- %
I _N	0,95 A	I _A / I _N	2,9
n	860 min ⁻¹		IP54
C _{400V}	-- μ F		01.006
t _R	55 °C		30 kg

Type : DVW/DHW 500-6-6 D		Art.-No. : A26-50058 / A36-50058	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₁	0,52/0,33 kW	ΔI	-- %
I _N	0,95/0,55 A	I _A / I _N	2,9
n	860/640 min ⁻¹		IP54
C _{400V}	-- μ F		01.045
t _R	55 °C		30 kg

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		f _m [Hz]						
		125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)]	Ansaugseite / inlet side	-17	-11	-11	-8	-9	-15	-21
LWA ₆ [dB(A)]	Ausblasseite / outlet side	-16	-8	-6	-5	-8	-14	-23

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		f _m [Hz]						
		125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)]	Ansaugseite / inlet side	-17	-11	-11	-8	-9	-15	-21
LWA ₆ [dB(A)]	Ausblasseite / outlet side	-16	-8	-6	-5	-8	-14	-23

