



Type : DVW/DHW 560-4 D		Art.-No. : A26-56010 / A36-56010	
U	400V (50Hz)	Δp_{fa} min	- Pa
P ₁	2.6 kW	ΔI	7 %
I _N	4.8 A	I _A / I _N	4.0
n	1330 min ⁻¹		IP54
C _{400V}	- μ F		01.006
t _R	40 °C		80 kg

Type : DVW/DHW 560-4-4 D		Art.-No. : A26-56052 / A36-56052	
U	400V (50Hz)	Δp_{fa} min	- Pa
P ₁	2.6/1.75 kW	ΔI	- %
I _N	4.8/2.9 A	I _A / I _N	4.0
n	1330/1070 min ⁻¹		IP54
C _{400V}	- μ F		01.045
t _R	40 °C		80 kg

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)]	Ansaugseite / inlet side	-17	-11	-11	-8	-9	-15	-21
LWA ₆ [dB(A)]	Ausblasseite / outlet side	-16	-8	-6	-5	-8	-14	-23

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)]	Ansaugseite / inlet side	-17	-11	-11	-8	-9	-15	-21
LWA ₆ [dB(A)]	Ausblasseite / outlet side	-16	-8	-6	-5	-8	-14	-23

