



Typ / Type: EHAE 355-4		Art.-Nr. / Art.-No.: B31-35500	
U	230V (50Hz)	$\Delta p_{fa \text{ min}}$	-- Pa
P ₁	0.39 kW	ΔI	19 %
I _N	1.80 A	I _A / I _N	2.1
n	1320 min ⁻¹		IP54
C _{400V}	8 μF		01.024
t _R	55 °C		22,5 kg

Typ / Type: EHAD 355-4		Art.-Nr. / Art.-No.: B30-28060	
U	400V (50Hz)	$\Delta p_{fa \text{ min}}$	-- Pa
P ₁	0.41 kW	ΔI	4 %
I _N	0.85 A	I _A / I _N	3.5
n	1370 min ⁻¹		IP54
C _{400V}	-- μF		01.006
t _R	60 °C		22,5 kg

LW _{Arel} A-bewertet bei V=0,5*V _{max} LW _{Arel} A-weighted at V=0,5*V _{max}	f _M [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-19	-6	-6	-5	-8	-18	-25
Ansaugseite 4-polig / inlet side 4-pole	-18	-8	0	-6	-6	-12	-21
Ausblasseite 2-polig / outlet side 2-pole	-21	-9	-2	-8	-12	-18	-25
Ansaugseite 2-polig / inlet side 2-pole	-13	-7	-5	-7	-8	-12	-18

