



Typ / Type : EHAE 400-4		Art.-Nr. / Art.-No. : B31-40000	
U	230V (50Hz)	$\Delta p_{fa \text{ min}}$	- Pa
P ₁	0.68 kW	ΔI	16 %
I _N	3.2 A	I _A / I _N	2.3
n	1280 min-1		IP54
C _{400V}	14 μF		01.024
t _R	55 °C		28,5 kg

Typ / Type : EHAD 400-4		Art.-Nr. / Art.-No. : B31-40050	
U	400V (50Hz)	$\Delta p_{fa \text{ min}}$	- Pa
P ₁	0.62 kW	ΔI	- %
I _N	1.3 A	I _A / I _N	3.5
n	1280 min-1		IP54
C _{400V}	- μF		01.006
t _R	60 °C		27 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax	fM [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-19	-6	-6	-5	-8	-18	-25
Ansaugseite 4-polig / inlet side 4-pole	-18	-8	0	-6	-6	-12	-21
Ausblasseite 2-polig / outlet side 2-pole	-21	-9	-2	-8	-12	-18	-25
Ansaugseite 2-polig / inlet side 2-pole	-13	-7	-5	-7	-8	-12	-18

