



Typ / Type: <b>EHAE 450-4</b>		Art.-Nr. / Art.-No.: <b>B31-45000</b>	
U	230V (50Hz)	$\Delta p_{fa}$ min	-- Pa
P <sub>1</sub>	1.1 kW	$\Delta I$	-- %
I <sub>N</sub>	5.1 A	I <sub>A</sub> / I <sub>N</sub>	2.1
n	1275 min <sup>-1</sup>		IP54
C <sub>400v</sub>	25 $\mu$ F		01.024
t <sub>R</sub>	40 °C		43 kg

Typ / Type: <b>EHAD 450-4</b>		Art.-Nr. / Art.-No.: <b>B31-45050</b>	
U	400V (50Hz)	$\Delta p_{fa}$ min	-- Pa
P <sub>1</sub>	1.05 kW	$\Delta I$	-- %
I <sub>N</sub>	2.0 A	I <sub>A</sub> / I <sub>N</sub>	3.2
n	1290 min <sup>-1</sup>		IP54
C <sub>400v</sub>	-- $\mu$ F		01.006
t <sub>R</sub>	55 °C		43 kg

LWA <sub>rel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LWA <sub>rel</sub> A-weighted at V=0,5*V <sub>max</sub>	f [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-19	-6	-6	-5	-8	-18	-25
Ansaugseite 4-polig / inlet side 4-pole	-18	-8	0	-6	-6	-12	-21
Ausblasseite 2-polig / outlet side 2-pole	-21	-9	-2	-8	-12	-18	-25
Ansaugseite 2-polig / inlet side 2-pole	-13	-7	-5	-7	-8	-12	-18

