



Typ / Type : EHND 400-2 (LG/RD)		Art.-No. : B37-40020 / B37-40021	
U	400V (50Hz)	$\Delta p_{fa}$ min	- Pa
P <sub>2</sub>	5.5 kW	$\Delta I$	- %
I <sub>N</sub>	10.5 A	I <sub>A</sub> / I <sub>N</sub>	5.9
n	2900 min-1		IP55
C <sub>400V</sub>	- μF		01.387
t <sub>R</sub>	40 °C		68 kg

Typ / Type : EHND 400-4 (LG/RD)		Art.-No. : B37-40040 / B37-40041	
U	400V (50Hz)	$\Delta p_{fa}$ min	- Pa
P <sub>2</sub>	0.75 kW	$\Delta I$	- %
I <sub>N</sub>	2.0 A	I <sub>A</sub> / I <sub>N</sub>	4.2
n	1390 min-1		IP55
C <sub>400V</sub>	- μF		01.430
t <sub>R</sub>	40 °C		21 kg

LW <sub>Arel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LW <sub>Arel</sub> A-weighted at V=0,5*V <sub>max</sub>	fM [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 2-polig / outlet side 2-pole	-26	-13	-6	-5	-5	-12	-22
Ansaugseite 2-polig / inlet side 2-pole	-22	-12	-4	-5	-8	-13	-21
Ausblasseite 4-polig / outlet side 4-pole	-21	-7	-6	-4	-9	-18	-27
Ansaugseite 4-polig / inlet side 4-pole	-17	-7	-5	-5	-9	-17	-25

Schaltbild / Wiring diagram:

Y-Schaltung /  
star-connection

