



Typ / Type : EHND 500-4 (LG/RD)		Art.-No. : B37-50040 / B37-50041	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₂	2.2 kW	ΔI	-- %
I _N	4.8 A	I _A / I _N	5.6
n	1410 min-1		IP55
C _{400V}	-- μ F		01.430
t _R	40 °C		49 kg

Typ / Type : EHND 500-6 (LG/RD)		Art.-No. : B37-50060 / B37-50061	
U	400V (50Hz)	Δp_{fa} min	-- Pa
P ₂	0.55 kW	ΔI	-- %
I _N	1.7 A	I _A / I _N	3.4
n	885 min-1		IP55
C _{400V}	-- μ F		01.430
t _R	40 °C		46 kg

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	fM [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-21	-7	-6	-4	-9	-18	-27
Ansaugseite 4-polig / inlet side 4-pole	-17	-7	-5	-5	-9	-17	-25
Ausblasseite 6-polig / outlet side 6-pole	-15	-3	-6	-4	-12	-20	-30
Ansaugseite 6-polig / inlet side 6-pole	-11	-4	-6	-7	-12	-22	-29

