



Typ / Type: EHND 560-4 (LG/RD)		Art.-No.: B37-56040 / B37-56041	
U	400V (50Hz)	$\Delta p_{fa \text{ min}}$	-- Pa
P ₂	3.0 kW	ΔI	-- %
I _N	6.4 A	I _A / I _N	5.6
n	1410 min ⁻¹		IP55
C _{400V}	-- μF		01.387
t _R	40 °C		66 kg

Typ / Type: EHND 560-6 (LG/RD)		Art.-No.: B37-56060 / B37-56061	
U	400V (50Hz)	$\Delta p_{fa \text{ min}}$	-- Pa
P ₂	1.1 kW	ΔI	-- %
I _N	3.0 A	I _A / I _N	3.8
n	910 min ⁻¹		IP55
C _{400V}	-- μF		01.430
t _R	40 °C		62 kg

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	f _M [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-21	-7	-6	-4	-9	-18	-27
Ansaugseite 4-polig / inlet side 4-pole	-17	-7	-5	-5	-9	-17	-25
Ausblasseite 6-polig / outlet side 6-pole	-15	-3	-6	-4	-12	-20	-30
Ansaugseite 6-polig / inlet side 6-pole	-11	-4	-6	-7	-12	-22	-29

