



Typ / Type : ERND 250-2 (LG/RD)		Art.-No. : B05-25020 / B05-25021	
U	400V (50Hz)	$\Delta p_{fa \text{ min}}$	245 Pa
P <sub>2</sub>	4.0 kW	$\Delta I$	- %
I <sub>N</sub>	7.8 A	I <sub>A</sub> / I <sub>N</sub>	6.8
n	2880 min <sup>-1</sup>		IP55
C <sub>400V</sub>	- μF		01.387
t <sub>R</sub>	40 °C		50 kg

Typ / Type : ERND 250-4 (LG/RD)		Art.-No. : B05-25040 / B05-25041	
U	400V (50Hz)	$\Delta p_{fa \text{ min}}$	250 Pa
P <sub>2</sub>	1.5 kW	$\Delta I$	- %
I <sub>N</sub>	3.5 A	I <sub>A</sub> / I <sub>N</sub>	5.3
n	1390 min <sup>-1</sup>		IP55
C <sub>400V</sub>	- μF		01.430
t <sub>R</sub>	40 °C		28 kg

LW <sub>Arel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LW <sub>Arel</sub> A-weighted at V=0,5*V <sub>max</sub>	fM [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-23	-10	-8	-4	-7	-9	-16
Ansaugseite 4-polig / inlet side 4-pole	-19	-11	-11	-5	-5	-8	-14
Ausblasseite 6-polig / outlet side 6-pole	-23	-10	-6	-6	-6	-8	-15
Ansaugseite 6-polig / inlet side 6-pole	-20	-18	-8	-5	-5	-8	-16

