




Typ / Type : <b>ERND 355-4 (LG/RD)</b>		Art.-No. : <b>B05-35540 / B05-35541</b>	
U	400V (50Hz)	$\Delta p_{fa \text{ min}}$	900 Pa
P <sub>2</sub>	5.5 kW	$\Delta I$	-- %
I <sub>N</sub>	11.1 A	I <sub>A</sub> / I <sub>N</sub>	6.3
n	1440 min <sup>-1</sup>		IP55
C <sub>400V</sub>	-- $\mu$ F		01.387
t <sub>R</sub>	40 °C		72 kg

LW <sub>Arel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LW <sub>Arel</sub> A-weighted at V=0,5*V <sub>max</sub>	f [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-23	-10	-8	-4	-7	-9	-16
Ansaugseite 4-polig / inlet side 4-pole	-19	-11	-11	-5	-5	-8	-14
Ausblasseite 6-polig / outlet side 6-pole	-23	-10	-6	-6	-6	-8	-15
Ansaugseite 6-polig / inlet side 6-pole	-20	-18	-8	-5	-5	-8	-16

