







Typ / Type: DRAD 356-4 K		Art.-Nr. / Art.-No.: C00-35640	
U	400V (50Hz)	Δp <sub>fa</sub> min	200 Pa
P <sub>1</sub>	3.2 kW	ΔI	-- %
I <sub>N</sub>	5.2 A	I <sub>A</sub> / I <sub>N</sub>	2.2
n	1020 min <sup>-1</sup>		IP54
C <sub>400V</sub>	-- μF		01.006
t <sub>R</sub>	40 °C		72 kg

Typ / Type: DRAD 356-4		Art.-Nr. / Art.-No.: C00-35643	
U	400V (50Hz)	Δp <sub>fa</sub> min	360 Pa
P <sub>1</sub>	4.2 kW	ΔI	4 %
I <sub>N</sub>	6.9 A	I <sub>A</sub> / I <sub>N</sub>	3.3
n	1230 min <sup>-1</sup>		IP54
C <sub>400V</sub>	-- μF		01.006
t <sub>R</sub>	40 °C		72 kg

LW <sub>Arel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LW <sub>Arel</sub> A-weighted at V=0,5*V <sub>max</sub>	fIM [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-23	-15	-9	-4	-6	-8	-15
Ansaugseite 4-polig / inlet side 4-pole	-20	-15	-11	-4	-5	-9	-14

