







Typ / Type : <b>DRAE 133-2</b>		Art.-Nr. / Art.-No. : <b>C00-13303</b>	
U	230V (50Hz)	$\Delta p_{fa}$ min	-- Pa
P <sub>1</sub>	0.24 kW	$\Delta I$	-- %
I <sub>N</sub>	0.95 A	I <sub>A</sub> / I <sub>N</sub>	1.1
n	1510 min <sup>-1</sup>		IP44
C <sub>400V</sub>	6 μF		01.009
t <sub>R</sub>	50 °C		4 kg

Typ / Type : <b>DRAE 133-4</b>		Art.-Nr. / Art.-No. : <b>C00-13301</b>	
U	230V (50Hz)	$\Delta p_{fa}$ min	-- Pa
P <sub>1</sub>	0.09 kW	$\Delta I$	-- %
I <sub>N</sub>	0.38 A	I <sub>A</sub> / I <sub>N</sub>	1.3
n	1160 min <sup>-1</sup>		IP44
C <sub>400V</sub>	2 μF		01.009
t <sub>R</sub>	60 °C		4 kg

LW <sub>Arel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LW <sub>Arel</sub> A-weighted at V=0,5*V <sub>max</sub>	fM [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-22	-13	-7	-4	-7	-9	-17
Ansaugseite 4-polig / inlet side 4-pole	-18	-10	-8	-5	-6	-9	-15

