



Typ / Type: ERAE 356-4		Art.-Nr. / Art.-No.: B20-35600	
U	230V (50Hz)	$\Delta p_{fa \text{ min}}$	220 Pa
P <sub>1</sub>	1.56 kW	$\Delta I$	-- %
I <sub>N</sub>	7.0 A	I <sub>A</sub> / I <sub>N</sub>	1.6
n	1135 min <sup>-1</sup>		IP54
C <sub>400V</sub>	25 $\mu$ F		01.025
t <sub>R</sub>	40 °C		35 kg

Typ / Type: ERAD 356-4		Art.-Nr. / Art.-No.: B20-35640	
U	400V (50Hz)	$\Delta p_{fa \text{ min}}$	100 Pa
P <sub>1</sub>	2.45 kW	$\Delta I$	-- %
I <sub>N</sub>	4.5 A	I <sub>A</sub> / I <sub>N</sub>	2.8
n	1270 min <sup>-1</sup>		IP54
C <sub>400V</sub>	-- $\mu$ F		01.006
t <sub>R</sub>	40 °C		35 kg

LW <sub>Arel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LW <sub>Arel</sub> A-weighted at V=0,5*V <sub>max</sub>	f [Hz]						
	125	250	500	1K	2K	4K	8K
Ausblasseite 4-polig / outlet side 4-pole	-22	-13	-7	-6	-5	-7	-15
Ansaugseite 4-polig / inlet side 4-pole	-20	-11	-9	-4	-7	-8	-15

